50-506

INSTRUCTION SHEET OFF VEHICLE CARBURETOR SERVICE ROCHESTER — MODEL 2G, 2GC

GENERAL EXPLODED VIEW

THE GENERAL DESIGN AND PARTS SHOWN WILL VARY TO INDIVIDUAL UNITS COVERED ON THIS INSTRUCTION SHEET

28-

DISASSEMBLY

USE EXPLODED VIEW AS A GUIDE. THE NUMERICAL SEQUENCE MAY GENERALLY BE FOLLOWED TO DISASSEMBLE UNIT FAR ENOUGH TO PERMIT CLEANING AND INSPECTION. NOTE: TO REMOVE PUMP ASSY. (46), TWIST UPSET END WITH SMALL PLIERS UNTIL IT BREAKS OFF. SERVICE PUMP WILL HAVE A RETAINING CLIP GROOVE. REMOVE STAKING FROM BOWL COVER FOR EASY REMOVAL OF POWER PISTON ASSEMBLY (41). IDLE LIMITER FROM BOWL COVER FOR EASY REMOVAL OF POWER HISTON ASSEMBLY (41). IDELEMINE CAPS (70) CAN EASILY BE REMOVED BY BREAKING OFF WITH A PAIR OF PLIERS. NO REPLACEMENT CAPS ARE NECESSARY AS A BARE MIXTURE SCREW IS SUFFICIENT TO INDICATE THAT THE MIXTURE HAS BEEN READJUSTED. BEFORE REMOVING IDLE ADJUSTING NEEDLES (71), TURN IN TO COUNT THE NUMBER OF TURNS NEEDLES ARE OUTFROM A SEATED POSITION. SOME MODELS IN 1980-81 WILL HAVE A PUMP LEVER SHAFT SEAL. USE A SMALL SCREW DRIVER TO PRY OUT THE OLD SEAL. AFTER CLEANING INSTALL NEW SEAL WITH THE ID OF SEAL BEGING OUTWARD. NEW SEAL WITH THE LIP OF SEAL FACING OUTWARD.

NOMENCLATURE

_			
REF		REF	•
NO.		NO.	
1.	SCREW (3)-CHOKE COVER	35.	BOWL COVER ASSY.
	RETAINER		PIN - FLOAT HINGE
2.	RETAINER (3)-CHOKE COVER	37.	FLOAT & LEVER ASSY.
3.	CHOKE COVER & SPRING ASSY.	38	NEEDLE, SEAT & GASKET ASSY
	GASKET - CHOKE COVER		GASKET-BOWL COVER
	SCREW (2)-CHOKE HOUSING		BAFFLE - FUEL
	CHOKE HOUSING ASSY.		POWER PISTON ASSY.
	SCREW - LEVER		PUMP LEVER SHAFT
	LEVER-INTERMEDIATE CHOKE		WASHER-PUMP SHAFT (NYLON)
9.	SHAFT ASSYINTERMEDIATE		LEVER - INNER PUMP
	CHOKE		RETAINER (SERVICE ITEM)
10.	SEAL-INTERMEDIATE CHOKE		PUMP ASSY.
	SHAFT		FITTING - FUEL INLET
	GASKET - CHOKE HOUSING		GASKET - FITTING
	ROD-INTERMEDIATE CHOKE		FILTER - FUEL
	SCREW-CHOKE SHAFT LEVER		SPRING - FUEL FILTER
	LEVER - CHOKE SHAFT		SPRING - PUMP RETURN
	LINK-AUX. VACUUM BREAK	52.	BALL-PUMP INTAKE CHECK
16.	SCREW (2)-AUX. VACUUM		(ALUM)
	BREAK		POWER VALVE ASSYMECH.
1/.	AUXILIARY VACUUM BREAK		GASKET - POWER VALVE
10			POWER VALVE ASSYVAC.
	HOSE-AUX. VAC. BREAK HOSE-PRI. VAC. BREAK		GASKET-POWER VALVE
	SCREW (2)-PRI. VAC.		JET (2) - MAIN SCREW & LOCKWASHER (2)-
20.	BREAK	>0.	VENTURI CLUSTER
21	PRIMARY VACUUM BREAK	50	SCREW-VENTURI CLUSTER
21.	ASSY.	29.	CENTER
• •		60.	GASKET - CENTER SCREW
	LINK-PRI. VAC. BREAK SCREW (2)-VENT COVER		VENTURI CLUSTER ASSY.
	COVER - VENT VALVE		GASKET-VENTURI CLUSTER
	GASKET - VENT COVER	63	INSERT (2)-MAIN WELL
	SPRING - VENT VALVE		GUIDE-PUMP DISC. SPRING
	VENT VALVE ASSY.		SPRING-PUMP DISC. BALL
	RETAINER - PUMP ROD		BALL-PUMP DISC. (STEEL)
	ROD - PUMP		SCREW & LOCKWASHER (3)-
30.	SCREW - FAST IDLE CAM		THROTTLE BODY
	CAM - FAST IDLE	68.	BOWL ASSY.
32.	ROD - CHOKE	69.	GASKET-THROTTLE BODY
33.	SCREW & LOCKWASHER (1)-	70.	CAP (2)-IDLE LIMITER
	BOWL COVER (LONG)	71.	NEEDLE (2)-IDLE ADJUSTING
34.	SCREW & LOCKWASHER (7)-		SPRING (2)-IDLE ADJ. NEEDL
	BOWL COVER		THROTTLE BODY ASSY.
	CLEAN	ING	
	ANING MUST BE DONE WITH CAR		TOP DISASSEMBLED. USE

CLEANING

CLEANING MUST BE DONE WITH CARBURETOR DISASSEMBLED. USE
A CARBURETOR CLEANING SOLVENT TO SOAK PARTS LONG ENOUGH TO
SOFTEN AND REMOVE ALL FOREIGN MATERIAL. MAKE CERTAIN THE
THROTTLE BORES ARE FREE OF ALL CARBON AND VARNISH DEPOSITS.
RINSE OFF IN SUITABLE SOLVENT. BLOW OUT ALL PASSAGES IN
CASTINGS WITH COMPRESSED AIR AND CHECK CAREFULLY TO INSURE
THOROUGH CLEANING OF OBSCURE AREAS. CAUTION: DO NOT SOAK
FLOAT, DIAPHRAGM UNITS, RUBBER OR PLASTIC PARTS IN SOLVENT.
DO NOT SAND, WIRE BRUSH, OR FILE ON TEFLON-COATED PARTS.

REASSEMBLE IN REVERSE ORDER OF DISASSEMBLY. NOTE SPECIAL INSTRUCTIONS AND FOLLOW NUMERICAL OUTLINE IN MAKING ADJUSTMENTS NECESSARY FOR CARBURETOR BEING SERVICED.

SPECIAL INSTRUCTIONS

IDLE ADJUSTING NEEDLES (71) - TURN EACH NEEDLE IN UNTIL LIGHTLY SEATED, THEN BACK OUT NUMBER OF TURNS COUNTED ON DISASSEMBLY.

PUMP RETURN SPRING (51) - INSTALL WITH LARGE END TO BOTTOM OF PUMP WELL.


POWER PISTON ASSY. WASHER. (41) - LIGHTLY STAKE CASTING AROUND





AIR HORN TIGHTENING SEQUENCE


INTERMEDIATE CHOKE SHAFT SEAL (10) - INSTALL SEAL WITH LIP


ADJUSTMENTS


























ADJUSTMENT DATA TABLE ROCHESTER CARBURETOR MODEL 2GC

Year	Application			Float Level	Float Drop	Pump Rod Setting	Primary Vacuum Break	Auxiliary Vacuum Break	Choke Rod	Unloader	Automatic Choke Setting
	BUICK						7.0				
1975	231" Eng. V6 Carb #7045145 Carb #7045147 231" Eng. V6 350" Eng. V8	Calif.	A/T M/T M/T A/T	7/16" 7/16" 7/16" 7/16" 15/32"	1 9/32" 1 9/32" 1 9/32" 1 9/32" 1 9/32"	1 19/32" 1 19/32" 1 19/32" 1 19/32" 1 19/32"	1/8" 3/16" 1/8" 1/8" 9/64"	1/8" 1/8" 1/8" 1/8" 1/8"	5/64" 5/64" 5/64" 5/64"	9/64" 9/64" 9/64" 9/64" 3/16"	1-RICH 1-LEAN 1-LEAN 1-LEAN 1-RICH
1976	231" Eng. V6 231" Eng. V6 350" Eng. V8	Federal Calif.	A/T	7/16" 7/16" 15/32"	1 5/32" 1 5/32" 1 5/32"	1 19/32" 1 19/32" 1 11/32"	7/64" 1/8" 9/64"	3/32" 7/64" 3/32"	5/64" 5/64" 5/64"	9/64" 9/64" 3/16"	1-RICH 1-RICH 1-RICH
1977	231" Eng. V6 Carb #17057141, 145, 147	Federal Calif. Calif. Altitude	A/T A/T M/T A/T A/T	7/16" 7/16" 7/16" 7/16" 7/16" 15/32"	1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32"	1 17/32" 1 1/2" 1 1/2" 1 1/2" 1 17/32" 1 9/16"	7/64" 7/64" 1/8" 9/64" 1/8" 9/64"	3/64" 3/64" 7/64" 7/64" 7/64"	5/64" 5/64" 5/64" 5/64" 5/64"	9/64" 9/64" 9/64" 9/64" 9/64" 3/16"	3-RICH 1-RICH 1-RICH INDEX 1-RICH 1-RICH
1978	350" Eng. V8 196" Eng. V6 196" Eng. V6 231" Eng. V6 231" Eng. V6 Carb #17058444 Carb #17058448	Fed/Can Federal Calif. Calif. Calif. Calif.	A/T M/T A/T M/T A/T A/T A/T A/T A/T/T	7/16" 7/16" 7/16" 7/16" 7/16" 7/16" 7/16" 7/16" 7/16"	1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32"	1 19/32" 1 9/16" 1 19/32" 1 19/32" 1 19/32" 1 19/32" 1 19/32" 1 19/32"	1/8" 7/64" 7/64" 7/64" 9/64" 1/8" 9/64" 5/32" 9/64"	3/64" 5/64" 5/64" 1/16" 3/32" 7/64" 3/32" 7/64" 3/32"	5/64" 5/64" 5/64" 5/64" 5/64" 5/64" 5/64" 5/64"	9/64" 9/64" 9/64" 5/32" 9/64" 9/64" 9/64" 9/64"	1-RICH 1-RICH 1-RICH 1-RICH 1-RICH 1-RICH 1-RICH 1-RICH 1-RICH
	CHEVROLET			2914-5-1		27			742 J. (3. (3. (3. (3. (3. (3. (3. (3. (3. (3	Marine Contract	~3.
1978	196" Eng. V6 196" Eng. V6 231" Eng. V6 231" Eng. V6 231" Eng. V6 231" Eng. V6 231" Eng. V6	Fed/Can Federal Calif. Calif. Altitude	A/T M/T A/T M/T A/T M/T	7/16" 7/16" 7/16" 7/16" 7/16" 7/16"	1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32" 1 5/32"	15/8" 19/16" 119/32" 119/32" 19/16" 119/32" 119/32"	7/64" 7/64" 7/64" 7/64" 9/64" 5/32" 9/64"	1/16" 5/64" 5/64" 1/16" 3/32" 7/64" 3/32"	5/64" 5/64" 5/64" 5/64" 5/64" 5/64' 5/64"	9/64" 9/64" 9/64" 5/32" 9/64" 9/64"	1-RICH 1-RICH 1-RICH 1-RICH 1-RICH 1-RICH 1-RICH
	CHEVROLET/GMC TRUCK					. 4	80		100		
1979	350" Eng. V8 w/Vac Gov	Fed/Calif.	All/T	17/32"	1 9/32"	1 15/32"					
1979-84	350" Eng. V8	Fed/Calif.	All/T	5/8"	1 9/32"	1 21/32"					
1980-82	350" Eng. V8 w/Vac Gov	Fed/Calif.	All/T	5/8"	1 9/32"	1 15/32"		·			
1980- 84	350" Eng. V8 Carb #17080129, 17082129			5/8"	1 9/32"	1 21/32"		.130	.245	.250	
1985-86	350" Eng. V8 Carb #17080126 Carb #17084433 , 17085126			5/8" 5/8"	1 9/32" 1 9/32"	1 15/32" 1 21/32"					==

Year	Applica	tion		Float Level	Float Drop	Pump Rod Setting	Primary Vacuum Break	Auxiliary Vacuum Break		Unloader	Automatic Choke Setting
, 001	CHEVROLET/GMC TRUCK			1							
4000 07		. (00									
1986-87	350" Eng. V8 Carb #17085464, 1708609	59		5/8"	1 9/32"	1 15/32"					
	Carb #17085465			5/8"	1 9/32"	1 21/32"					
1988-90	350" Eng. V8										
	Carb #7044133	Canada		11/16"	1 9/32"	1 9/16"					
	Carb #17058120 Carb #17088079	Canada		11/16" 5/8"	1 9/32" 1 9/32"	1 7/16" 1 15/32"			==		
	Carb #17788080			5/8"	1 9/32"	1 21/32"					
	OLDSMOBILE				-						
1975	231" Eng. V6		A/T	7/16"	1 9/32"	1 19/32"	1/8"	1/8"	5/64"	9/64"	1-RICH
1373	231 Ling. VO		M/T	7/16"	1 9/32"	1 19/32"	1/8"	1/8"	5/64"	9/64"	1-LEAN
	350" Eng. V8		A/T	15/32"	1 9/32"	1 19/32"	9/64"	1/8"	5/64"	3/16"	1-RICH
1976	231" Eng. V6										
	Carb #7045147, 449			7/16"	1 9/32"	1 19/32"	1/8"	1/8"	5/64" 5/64"	9/64" 9/64"	1-LEXN
	Carb #7045149		A/T A/T	7/16" 7/16"	1 9/32"	1 19/32" 1 19/32"	1/8" 1/8"	1/8" 7/64"	5/64"	3/16"	1-RICH 1-RICH
	Carb #7045441 Carb #7045447		M/T	7/16	1 9/32"	1 19/32"	1/8"	1/8"	37/64"		1-LEAN
	Carb #17056145, 149		141/	7/16"	1 5/32"	1 19/32"	7/64"	3/32"	5/64"	9/64"	1-RICH
	Carb #17056447, 449			7/13"	1 5/32"	1 19/32"	1/8"	7/64"	5/64"	9/64"	1-RICH
	350" Eng. V8										
	Carb #17056143		A/T A/T	15/32"	1 5/32"	1 9/16" 1 5/8"	9/64" 3/16'	7/64" 1/32"	5/64" 5/64"	3/16" 3/16"	1-RICH 1-RICH
	Carb #17056144		A/1	15/32"	1 5/32"	15/6	3/10	1/32	3/04	3/10	1-MCH
1977	231" Eng. V8	Federal	A/T	7/15"	15/32"	1 17/32"	7/64"	3/64"	5/64"	9/64"	3-RICH
		reaciai	M/T	7/18"	1 5/32"	1 1/2"	7/64"	3/64"	5/64"	9/64"	1-RICH
		Calif.	A/T	7/13"	1 5/32"	1 1/2"	1/8"	7/64"	5/64"	9/64"	1-RICH
		Calif.	M/T	7/18"	1 5/32."	1 1/2"	9/64"	7/64"	5/64"	9/64"	INDEX
		Altitude	A/T	7/13"	1 5/32"	1 17/32"	1/8"	7/64"	5/64"	9/64"	1-RICH
1978	231" Eng. V6	- 1/0		7/40"	1.5/00#	1 10/22"	7/64"	5/64"	5/64"	9/64"	1-RICH
		Fed/Can Federal	A/T M/T	7/16" 7/16"	1 5/32" 1 5/32"	1 19/32" 1 19/32"	7/64" 7/64"	1/16"	5/64"	5/32"	1-RICH
	Carb #17058444	Calif.	A/T	7/16"	1 5/32"	1 19/32"	9/64"	3/32"	5/64"	9/64"	1-RICH
	Carb #17058446	Calli.	A/T.	7/13"	1 5/32"	1 19/32"	1/8"	7/64"	5/64"	9/64"	1-RICH
	Carb #17058448 •		A/T	7/16"	1.5/32"	1 9/16"	9/64"	3/32"	5/64"	9/64"	1-RICH
		Calif.	M/T	7/16"	1 5/32"	1 19/32"	5/32"	7/64"	5/64"	9/64"	1-RICH
		Altitude	· All/T	7/16"	1 5/32"	1 19/32"	9/64"	3/32"	5/64"	9/64"	1-RICH
	PONTIAC				571						
1975	350" Eng. V8		A/T	9/16"	1 7/32"	1 9/32"	9/64"	17/64"	3/32"	3/16" 3/16"	1-RICH
	Carb #7045143		A/T A/T	15/32" 9/13"	1 9/32" 1 7/32"	.1 19/32" 1 11/32"	9/64" 9/64"	1/8" 17/64"	5/64" 3/32"	3/16"	1-RICH 1-RICH
1976	400" Eng. V8 231" Eng. V6	Federal		7/13"	1 5/32"	1 19/32"	7/64"	3/32"	5/64"	9/64"	1-RICH
1970	231 Eng. Vo	Calif.		7/13"	1 5/32"	1 19/32"	1/8"	7/64"	5/64"	9/64"	1-RICH
	350" Eng. V8					40/40"	0/04#	7/04"	F /C 4"	2/10"	1 DICU
	Carb #17056143		A/T	15/32"	1 5/32"	1 9/16" 1 11/32"	9/64" 9/64"	7/64" 17/64"	5/64" [/32"	3/16" 3/16"	1-RICH 1-RICH
	Carb #7045163, 173 Carb #17056161, 162		A/T A/T	9/13" 9/13"	1 7/32" 1 9/32"	1 11/32"	11/64"	9/32"	3/32"	3/16"	1-RICH
	Carb #17056161, 102		A/T	9/15"	1 9/32"	1 11/32"	9/64"	9/32"	3/32"	3/16"	1-RICH
	Carb #17056144		A/T	15/32"	1 5/32"	1 5/8"	3/16"	1/32"	5/64"	3/16"	1-RICH
	400" Eng. V8										4 51611
	Carb #7045167		A/T	9/16"	1 7/32"	15/16"	9/64"	5/16"	3/32" 3/32"	3/16" 3/16"	1-RICH 1-RICH
	Carb #17056160, 164		A/T	9/16"	1 9/32"	1 11/32"	11/64"	9/32"	5/64"	9/64"	3-RICH
1977	231" Eng. V6	Federal	A/T M/T	7/16" 7/16"	1 5/32" 1 5/32"	1 17/32" 1 1/2"	7/64" 7/64"	3/64"	5/64"	9/64"	1-RICH
		Calif.	A/T	7/16"	1 5/32"	1 1/2"	1/8"	7/64"	5/64"	9/64"	1-RICH
		Calif.	M/T	7/16"	1 5/32"	1 1/2"	9/64"	7/64"	5/64"	9/64"	INDEX
		Altitude	A/T	7/16"	1 5/32"	1 17/32"	1/8"	7/64"	5/64"	9/64"	1-RICH
1978	231" Eng. V6	Fed/Can	A/T	7/16"	1 5/32"	1 19/32"	7/64"	5/64"	5/64"	9/64"	1-RICH
		Federal	M/T	7/16"	1 5/32"	1 19/32"	7/64"	1/16"	5/64"	5/32"	1-RICH
	Carb #17058444	Calif.	A/T	7/16"	1 5/32"	1 19/32"	9/64"	3/32"	5/64" 5/64"	9/64" 9/64"	1-RICH 1-RICH
	Carb #17058446		A/T A/T	7/16" 7/16"	1 5/32" 1 5/32"	1 19/32" 1 9/16"	1/8" 9/64"	7/64" 3/32"	5/64"	9/64"	1-RICH
	Carb #17058448	Calif.	M/T	7/16"	1 5/32"	1 19/32"	5/32"	7/64"	5/64"	9/64"	1-RICH
		Altitude	All/T	7/16"	1 5/32"	1 19/32"	9/64"	3/32"	5/64"	9/64"	1-RICH